



Remote Display Unit Model BI-1240

Features

The Bintech Remote Display Unit BI-1240 provides a power supply display for operation in a safe area. It is especially suitable for monitoring tank contents when used in conjunction with the BI-2000 series tank sensors. The display is readily visible in bright and low light locations. The unit can be mains powered from 240 Vac. It is able to power an instrument loop. The Bintech BI-1240 display indicator is designed and manufactured in Australia.

Specifications

| Characteristic | Detail |
|------------------------|--|
| Enclosure: | PVC, surface mount |
| Environment: | Internal (non hazardous area) |
| Cable Access: | Bottom or side entry |
| Display: | 3.5 Digit LCD 13 mm high |
| Display Range: | Preset Maximum within the range 0.00 to 1999 |
| Decimal Point: | Preset 0, 0.0, 0.00 by link |
| Loop Current Sense: | 4 to 20 mA DC |
| Calibration: | 4 and 20 mA points |
| Output Loop Voltage: | >18 V @ 26mA DC max |
| Accuracy: | ±0.1% of max. displayed value ± 1 digit |
| Temp. Coefficient: | 0.03% / °C |
| Operating Temperature: | 0°C to 50°C |
| Power Requirements: | 240 VAC 50/60 Hz 7VA |
| Dimensions: | H x W x D, 150 x 110 x 75 mm |
| Weight: | Approx. 0.8kg |



Ordering Information

Model Code: BI-1240-240



Bintech Systems Pty Ltd
ABN 74 123 478 431

5 / 58 Mahoney Road
Thomastown VIC 3074
Australia

T: +613 9467 7300
T: 1300 363 163
sales@bintech.com.au
www.bintech.com.au



Version 4_Dec 2020